



SB33 Luminaire



SB33

<u>SPECIFICATIONS</u>

DESCRIPTION

The luminaire shall consist of a ballast/ reflector housing and a pendant style globe. There shall be an internal reflector with horizontal lamp.

DIMENSIONS

Fixture dimensions shall be as shown on back page.

MATERIALS

The ballast/reflector housing shall be heavy wall, copper free, cast aluminum produced from certified ASTM 356.1 ingot per ASTM B-179-95A or ASTM B26-95, formed true to the pattern with complete detail. Globe material shall be clear textured in acrylic or polycarbonate. The reflector shall be hydroformed, polished and anodized aluminum. All hardware shall be stainless steel.

INSTALLATION

The luminaire shall have 1.5" female, NPT at top for mounting. The globe shall be gasketed and mounted on an aluminum ring which is hinged to the hood for easy relamping. The ballast and socket assembly shall be furnished with a quick disconnect plug and mount on a removable ballast plate.

<u>FINISH</u>

For finish specifications and color options see **"Finish"** section in catalog.

LIGHT SOURCE

Luminaries shall be furnished with an H.I.D. ballast and socket assembly. Luminaire shall be UL listed and labeled as suitable for wet locations. Sockets shall be glazed porcelain, mogul or medium base, with a copper alloy nickel plated screw shell and center contact. Ballast shall be core and coil, high power factor, regulating type.



SB33 Luminaire

