



W11-2



W16-7P



R1-6

R1-6 TO BE USED AT MID-BLOCK, HIGH VOLUME, OR TO INCREASE VISIBILITY

W11-2 & W16-7P
SIGNS REQUIRED

OVERHEAD
DECORATIVE
HOKIE LIGHT
POLE
(BY VTES)

A

SIDEWALK

CENTERLINE
OF ROAD

24" SOLID WHITE
THERMOPLASTIC
CROSSWALK LINE

24" BTWN STRIPES
(TO BE PLACED TO
AVOID WHEEL PATH)

6'-10' (TYP.),
20' (INFINITE LOOP)

R1-6

VARIABLE LANE VARIABLE LANE

FACE-TO-FACE

DIRECTION OF
TRAVEL

OVERHEAD
DECORATIVE
HOKIE LIGHT
POLE
(BY VTES)

W11-2 & W16-7P
SIGNS REQUIRED

CROSSWALK
(HORIZONTAL)

EXPANSION JOINT

PROPOSED OR
EXISTING SIDEWALK
USE VT STANDARD
FOR PROPOSED
SIDEWALKS

VARIABLE

STANDARD 2.5' CURB
& GUTTER (CG-6)

DEPRESSED CURB

4"

WHEELCHAIR RAMP.
SLOPE NOT TO EXCEED
12:1. Min. 36" WIDE

SECTION A-A

5' MIN WIDE
PROPOSED OR
FUTURE SIDEWALK

4' x 4'

LANDING

4' MIN

RAMP WIDTH

6' MIN WIDE
CROSSWALK

2' x 4' TRUNCATED
DOMES MAT USE VT
STANDARD

CURB RAMPS STANDARD DETAILS

NOTE: INSTALL LAMP POST PER VIRGINIA TECH LIGHTING STANDARDS

STANDARD CROSSWALK

DRAWN NOT TO SCALE

CONSULT WITH VIRGINIA TECH OFFICE OF UNIVERSITY PLANNING FOR FURTHER DETAILS